


NOTES

- 1. ALL PLUGS SHALL BE CONCRETE OR BRICK AND MORTAR.
- SIDE SEWERS LARGER THAN 6" IN DIAMETER SHALL BE PLUGGED AND FILLED WITH EITHER SLURRY AS SPECIFIED IN SECTION 302 OF THE STANDARD SPECIFICATIONS OR PER CONTRACT DOCUMENTS.

This Standard Plan was developed for use on public works projects in the City and County of San Francisco, and shall not be used without consulting a Registered Professional Engineer. The Department of Public Works reserves the right to make revisions to this Standard Plan at any time.

					REFERENCE INFORMATION & FILE NO. OF SURVEYS
					W FIEL IVO. OF CONVETE
NO.	DATE	DESCRIPTION	BY	APP.	
	CHE(TABLE OF REVISIONS CK WITH TRACING TO SEE IF YOU HAVE LATEST REVISION			



BUREAU OF ENGINEERING DEPARTMENT OF PUBLIC WORKS

CITY AND COUNTY OF SAN FRANCISCO

EVIEWED:	DATE:	PLANS APPROVAL DATE: APRIL 30, 2007
	12/2006	Jun 5- 4/30/07
RAWN:	DATE:	SECTION MANAGER
A	07/2003	
HECKED:	DATE:	DEPUTY BUREAU MANAGER
S	12/200	BUREAU MANAGER

STANDARD PLAN	OLD FILE NO.	
HYDRAULICS	L-38,782 C	
ABANDONMENT OF EXISTING SIDE SEWER	FILE NO. 87,198 REV. NO.	